HANDLES & METERS: GREASE High Pressure Grease Handle





High Pressure Grease Handles High pressure grease dispenses handle with ergonomic body and trigger designed to reduce operator hand fatigue. Manufactured in aluminum with steel insert for high pressure.

Oval gear grease meter for all types of grease, with digital display and ergonomic grip. Progressive opening valve for excellent control of grease delivery. The gun includes inlet z-swivel and outlet hose with zerk connector.







413 077

413 081

413 082



	Metered	Non-Metered
Maximum flow rate	2.2 lb/min (1 Kg/min)	
Maximum working pressure	7,250 psi (500 bar)	7,250 psi (500 bar)
Inlet	1/4" NPT(F)	1/4" NPT(F)
Outlet	1/8" NPT(F)	1/8" NPT(F)
Accuracy	+/- 3.0%	
Power Source	2x "AAA" 1.5 Batteries	
Wetted parts	Aluminum, Stainless Steel	Aluminum, Stainless Steel
Manual	M00091	M00091

ORDER INFORMATION		
413 077	Grease Control Handle, 3-Jaw Coupler	
413 080	Grease Control Handle, 3-Jaw Coupler, Rigid Outlet	
413 081	Grease Control Handle, 3-Jaw Coupler, 18" Steel Braided Hose	
413 082	Grease Control Handle, 3-Jaw Coupler, 18" Steel Braided Hose, Z-Swivel	
1177	Grease Control Handle, 3-Jaw Coupler, 18" Steel Braided Hose, Z-Swivel, In-line Grease Meter	



• Fleet service

- · Lube trucks
- Mining equipment maintenance
- Truck dealerships
- Maintenance shops
- Mass transit maintenance
- Railroad

MARKETS SERVED

• Grease

120

FLUIDS HANDLED

Technical specifications are subject to change without prior notice