



Electronic PreSet Control Handle

Fluids Handled

- Motor Oil
- Hydraulic Oil
- Gear Oil
- Transmission Fluid
- Anti-freeze solutions
- Glycol

Models Available

| | |
|---------|--|
| 365 310 | Preset Meter, no outlet |
| 365 316 | Preset meter, rigid outlet with 1/4 turn non-drip tip |
| 365 317 | Preset meter, formable outlet with 1/4 turn non-drip tip |



Features

Durable handle design

- Quality components provide a long and reliable life.
- Overpressure and overload protection.

Easy and intuitive programming

- 6-key integrated keypad with large LCD screen.

Durable cast body

- Aluminum die cast for longer life and lighter weight.

1/2" High flow inlet swivel

- Heavy duty inlet swivel with inlet filter.

Protective TPE shroud for increased durability

Protective TPE swivel boot

- Prevents accidental scratches on vehicle body.

Easy to operate

- Four finger trigger for increased user comfort.

Long life batteries

- Works with four AA alkaline standard batteries.

Reliable valve operation

- Valve automatically shuts off once the delivered flow reaches the preset volume.

Two Line LCD

- Large character batch display. Smaller character totalizer. Can be programmed to measure in Gallons, Quarts, Pints or Liters.

Battery level indicator

- Informs when battery level is low.

Can store up to 10 preset values in memory

- Faster operation, simply recall the desired volume.

Transaction history

- Keeps in memory the last 5 transactions, storing time, date and volume delivered.



Easy to Replace Batteries

Four "AA" standard alkaline batteries provide the power required for an effective valve operation

Specifications

| | |
|-----------------------------------|---|
| Flow range | 0.2 to 8 gal/min (0.8 to 30 l/min) |
| Maximum working pressure | 1,425 psi (100 bar) |
| Units of measure | US Gallons, Quarts, Pints, Liters |
| Accuracy / Repeatability | ± 0.5 % |
| Inlet | 1/2" NPT (F) |
| Outlet | 1/2" NPT (F) |
| Maximum totalizer | 999999 units |
| Maximum recorded dispense | 999.9 units |
| Different preset values in memory | 10 |
| Working temperature range | 14 to 140° F (-10 to 60°C) |
| Battery | 4 x "AA" alkaline |
| Wetted parts | Aluminum, AISI316 stainless steel; Buna-N; Delrin, brass, zinc plated steel |
| Dimension (with no outlet) | L11.7" x W3.5" x H6" (L297 x W88 x H152 mm) |
| Weight (with no outlet) | 3.7 lb (1.7 kg) |

