



# Product Specification

## FS53014

Fuel/Water Separator

Fleetguard® FS53014 Elemax™ stacked filter removes harmful contaminants improving reliability, service intervals and fuel efficiencies, and reducing costs. Its patented control valve provides more complete use of the filter and has multiple micron ratings for OEM compliance and biodiesel compatible.



<b>Media Type</b>	NanoNet
<b>Largest OD</b>	5.83 inch
<b>Largest End ID</b>	1.54 inch
<b>Length</b>	16.20 inch
<b>Gasket Inside Diameter</b>	1.49 inch
<b>Gasket OD</b>	1.63 inch
<b>Flow Direction</b>	Outside In
<b>Length / Overall Height</b>	16.20 inch

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties,

express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved