Fleetguard® | Product Specification

FS53015

Fuel/Water Separator

Fleetguard® FS53015 standard size EleMax™ fuel filter protects vital fuel system components. Its patented control valve provides full use of the filter, fits Industrial Pro FH239 models, has multiple micron ratings for OEM compliance, and is biodiesel compatible.

Media Type	StrataPore
Length	8.59 inch
Largest OD	5.83 inch
Largest End ID	5.83 inch
Gasket Inside Diameter	1.49 inch
Gasket OD	1.63 inch
Flow Direction	Outside In
Length / Overall Height	8.59 inch

This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Cummins Filtration customers "as is" without any warranties,

express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved