



Pleated Paper Cartridge
 Part Number: PL718-10FPB
 Micron Rating: 10 Micron nominal
 Support structure: Plated Steel
 Media: Cellulose
 Gasket: Buna-N
 Max Temp: -20°F to +250°F
 Replacement Differential Pressure: 25 PSID (172 KPa)
 Element Collapse Pressure: 70 PSID (482 KPa)
 Direction of flow: Outside → In



Property of FAA Filters LLC
 200 Westshore Blvd., Newark, New York 14513
 Telephone 800-265-8943 Fax 315-331-4750
 This print is provided on a restricted basis. It is not to be used in any way detrimental to the interest of FAA Filters LLC.
 Confidential document, Duplication prohibited

FAA Filters LLC reserves the right to change design and/or specifications without notice

ORIGINAL ISSUE		<h2>Refilco Cartridges</h2> <h3>Pleated Paper Cartridge</h3>			
DRAWN:	BAR 12/12/2007				
CHECKED:	REH 9/26/2023				
APPROVED:	REH 9/26/2023	DRAWING NUMBER		DRAWING TYPE	REVISION
UNLESS OTHERWISE NOTED BREAK EDGES/REMOVE BURRS UNITS: LINEAR INCHES; ANGULAR DEGREES GENERAL TOLERANCES:±		PL718-10FPB		GA	~
FRACTIONAL: ~	DECIMAL: ~	SHEET SIZE	NUMBER	SCALE	STATUS
ANGULAR: ~	REFERENCE: (X)	A	1 OF 1	NOTED	

2

1