

NOTES:

- 1. TANK IS DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH U.N. SPECIFICATIONS.
- 2. TANK AND HEADS CONSTRUCTION OF 10 GA MATERIAL.
- 3. TANK IS AIR TESTED AT 3 PSI.
- 4. ALL WELDS CLEANED OF SLAG AND SPATTER.
- 5. TANK INTERIOR AND EXTERIOR ARE ELECTRO-CLEANED.

© SNYDER INDUSTRIES INC., 2015					304SS STD 3INFV	
Released KB			КВ	INDUSTRIES, INC.	ASM TK 126G SPRTNR 42X48	
NO.			DRAWN BY	REVIS		
ITEM			ER	DESCRIPTION		
1	1	34900498		TK 126 SPRTNR 42X48 304SS 6-3/16 LEG ELB		
2	1	35901173		VALVE GUARD 4-1/4 X 43-1/4 X 10GA 304SS		
3	1	34900029		WELD ASM LIFT LUGS SII STD 304SS		
4	1	36500069		SNYDER IBC UN TAG 304SS		
5	1	35400242		VALVE 2IN REV-STEM BV LOCKHNDL 316SS SII		
6	1	34200833		PLUG PVC 2IN NPT SQ HEAD		
7	1	35901290		ASM LID 22-5/16 DOT 3IN FV W/TEF 304SS		
8	1	33100387		GASKET 22-5/16 DIA 55 MS MULTISEAL EPDM		
9	1	35901511		PLUG 2IN HEX HEAD WH EPDM GASKET 304SS		
10	1	34701360		ASM BOLTED CLAMP RING 22-5/16 ZINC-PLTD		
11	1	34701719		DECAL PKG SII STD SPRTNR REV-STEM		
12	1	99700352		DECAL STACK 126 SPRTNR		
٥.	IA	ANN INTERIOR AND EXTERIOR ARE ELECTRO-CLEANED.				

(402) 467-5221 ww.snydernet.coi 6984000B51320

D003202