


## NOTES:

5.

 TANK SPEC
TANK
TANK
ALL \



ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE. ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A  $\pm$  3% TOLERANCE.

ID INFORMATION ON THIS PRINT MUST BE SNYDER INDUSTRIES, INC. AND MAY NOT TED WITHOUT WRITTEN PERMISSION OF AN HE FIRM.		(402) 467-5221 www.snydernet.com	6984000B51318	ENG. ID. D003194	
NDUSTRIES INC., 2015					1 OF 1
ed	КВ	INDUSTRIES, INC.	ASM TK 245 SPRTNR 42X48 B 304SS STD FV		
SCALE	DRAWN BY	STT SNYDER	TITLE:		REVISION
PART NUMBER		DESCRIPTION			
1900138		TK 245 SPRTNR 42X48 304SS STD LEG			
5901173		VALVE GUARD 4-1/4 X 43-1/4 X 10GA 304SS			
1900029		WELD ASM LIFT LUGS SII STD 304SS			
500069		SNYDER IBC UN TAG 304SS			
5400162		VALVE 2IN REV STEM BV LOCK HNDL 316SS			
1200833		PLUG PVC 2IN NPT SQ HEAD			
3100387		GASKET 22-5/16 DIA 55 MS MULTISEAL EPDM			
5901290		ASM LID 22-5/16 DOT 3IN FV W/TEF 304SS			
4701360		ASM BOLTED CLAMP RING 22-5/16 ZINC-PLTD			
5901511		PLUG 2IN HEX HEAD WH EPDM GASKET 304SS			
4701719		DECAL PKG SII STD SPRTNR REV-STEM			
700577		DECAL STACK RATING 245 SPRTNR			

ALL WELDS CLEANED OF SLAG AND SPATTER. TANK INTERIOR AND EXTERIOR ARE ELECTRO-CLEANED.

TANK AND HEADS CONSTRUCTION OF 10 GA MATERIAL. TANK IS AIR TESTED AT 3 PSI.

SPECIFICATIONS.

TANK IS DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH U.N.