




PUMPFLEX® MARINA – SOFTWALL

Color coded green primarily for marina use, this durable softwall hose is designed to handle severe weather conditions, rough deck or dock use. It has a durable four spiral construction and static wire for continuity, and its UL-approved cover is oil and weather resistant. The Pumpflex® Marina can be used for all types of gasoline, oil and other petroleum products.



Representative image photos see BRANDING below for product stamp.

<p>RESISTANCE</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  Gasoline </div> <div style="text-align: center;">  Oil </div> <div style="text-align: center;">  Weathering </div> </div> <p>BRANDING: Thermoid Size Pumpflex Marina Hose UL Listed 97MO Made In USA Month/Year</p> <p>COVER COLOR: Green</p> <p>MANUFACTURED: Oneida, TN</p>	<p>CONSTRUCTION</p> <p>TUBE: Nitrile Blend, ARPM - Class A</p> <ul style="list-style-type: none"> • High Oil Resistant • Handles Gasoline • Handles Oil • Handles Other Petroleum Products <p>COVER: Chlorinated Polyethylene, ARPM - Class A</p> <ul style="list-style-type: none"> • Medium-High Oil Resistant • Weather Resistant <p>REINFORCEMENT: 4-Spiral Polyester Yarn with Static Wire (Softwall)</p> <ul style="list-style-type: none"> • Provides a Working Pressure to 150 to 200 psi 	<p>TEMPERATURE RANGE: -40°F to +180°F, -40°C to +82°C</p> <p>PACKAGING: Reels</p> <ul style="list-style-type: none"> • Color Codes this Hose for Marina Use <p>STATIC WIRE, ALL SIZES</p> <ul style="list-style-type: none"> • Enables User to Ground the Hose, Dissipating a Build Up of Electricity
--	--	--

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	Reels (ft.)	(Inches)	(mm)	(Inches)	(mm)		(psi)	(Mpa)	(Inches)	(mm)	(lb/ft)	(Kg/m)
22463484662	500	3/4	19.05	1.13	28.58	4	200	1.38	4.50	114.30	0.32	0.48
22464644662	500	1	25.40	1.50	38.10	4	150	1.03	7.00	177.80	0.62	0.92